



Beautifies, protects, and extends the service life of asphalt roads

OptiPave Uses:

- Low-Traffic Roads
- Low-Traffic Streets
- Neighborhoods
- Gated Communities
- Highway Shoulders
- Cul-de-sac Roads
- Top Coat for Slurry and Chip Seal
- Airport Taxiways

MIXING PROCEDURES: OptiPave is ready to use. Do not dilute.

MATERIAL REQUIREMENTS (coverage): One gallon of OptiPave will cover approximately 50 - 75 square feet (5.55 to 8.33 square yards) per gallon.

OPTIPAVE™

SURFACE SEALER FOR ROADS

ECO-FRIENDLY ROAD SURFACE SEALER FOR PAVEMENT PRESERVATION

Advantages:

- Replenishes the valuable asphalt binder or "glue" that is lost through weathering, aging, traffic wear and other forms of environmental distress
- Fast, efficient, one-coat application process with minimal impact on traffic flow
- Provides a deep, rich, "like new" black appearance



PRODUCT #	DESCRIPTION	WEIGHT	PRICE
S1900P	5 - Gallon Pail	50 lbs.	\$46.99
S1900D	55 - Gallon Drum	555 lbs.	\$469.99
S1900B	Bulk	-	- quoted -