




ASK ABOUT  
**PMM**  
**ULTRA**  
FACTORY BLENDED  
WITH SAND ADDED


THE INDUSTRY'S #1 CHOICE FOR  
QUALITY & PERFORMANCE



Applied at higher solids than conventional sealer

**POLYMER-MODIFIED MASTERSEAL™ (PMM)**

ASPHALT BASED PAVEMENT SEALER



POLYMER MODIFIED FOR MAXIMUM DURABILITY

**Advantages:**

- Added strength, adhesion, flexibility, fuel resistance, and UV resistance
- Deep, rich black color

**Blended with polymers for superior adhesion, flexibility, and durability**

**Polymer-Modified MasterSeal Uses:**

- Parking Lots
- Driveways
- Low-Traffic Roads
- Low-Speed Roads
- Airports
- Shopping Malls
- Highway Shoulders

**MIXING PROCEDURES:**


*[Based on 100 gallons of Polymer-Modified MasterSeal]*  
PMM ..... 100 gallons  
Sand [40-70 mesh AFS].....200-400 lbs.

**NOTE:** If required, a small amount of water may be added to facilitate application of mixed material.

**MATERIAL REQUIREMENTS:** One gallon of PMM will cover approximately 85 - 95 square feet [9.4 to 10.5 square yards] per coat when properly mixed as a sand-filled coat and applied.

**NOTE:** Coverage rate may vary due to pavement age, porosity, and method of application.

**UNSEALED VS. SEALED**



PMM replenishes the binder that is lost through weathering and aging and provides a barrier to moisture intrusion as well as ultraviolet rays, chemicals and salt. PMM beautifies pavement, enhancing the image and curb appeal of commercial properties, home driveways, roadways and more.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
S1097P	5 - Gallon Pail	51 lbs.	\$42.99
S1097D	55 - Gallon Drum	565 lbs.	\$431.99
S1097B	Bulk	-	- quoted -