

## SM-30 DIRECT FIRE MELTER

IDEAL FOR USE WITH CRACKMASTER™ SUPREME DIRECT FIRE CRACK SEALANT

### **SM-30 Features:**

- Burner, hose and regulator
- 30-gallon capacity
- Hand operated agitator
- Retractable carrying handles
- Designed for use with Vapor LP gas cylinder (not included)
- Melting Rate is approximately 1/2 hour

| PRODUCT # | DESCRIPTION              | WEIGHT   |
|-----------|--------------------------|----------|
| E2800     | SM-30 Direct Fire Melter | 315 lbs. |
|           |                          |          |

\* Call for pricing

# SPECIFICATIONS: Height 30" Width 23" Length 48" Weight 315 lbs



# MA-10 MELTER APPLICATOR

IDEAL FOR MELTING AND APPLYING CRACKMASTER™ SUPREME DIRECT-FIRE CRACK SEALANT

## **MA-10 Melter Applicator Features:**

- Burner, hose and regulator
- 10-gallon capacity
- Hand operated agitator
- Designed for use with Vapor LP gas cylinder (not included)
- Melting Rate is less than 1/2 hour

| PRODUCT #          | DESCRIPTION             | WEIGHT   |
|--------------------|-------------------------|----------|
| E2820              | MA-10 Melter Applicator | 129 lbs. |
| * Call for pricing |                         |          |

| DIMENSIONS: |    |
|-------------|----|
| Height      | 39 |
| Width       | 24 |
| Length      | 43 |

Requires LP gas cylinder