

SPRAYMASTER™ TANKS WITH PRO-AIR SYSTEM

SKID-MOUNTED SEALCOAT SPRAY SYSTEM APPLICATORS

DESIGNED TO MIX AND APPLY PAVEMENT SEALER WITH OR WITHOUT SAND

SprayMaster Features:

- Dependable, low-maintenance, air-driven dual diaphragm pump.
 Shifts to neutral automatically when wand or spray bar is shut off. Sprays sand-filled pavement sealers.
- Hydraulically controlled, full-sweep agitation with rubber wiper blades
- 75-foot hose and spray wand

PRODUCT #	DESCRIPTION	WEIGHT				
E1320	SK 575 Pro-Air	2,240 lbs.				
E1330	SK 750 Pro-Air	2,340 lbs.				
E1340	SK 1,000 Pro-Air	3,200 lbs.				
E1360	SK 1,500 Pro-Air	3,700 lbs.				
E1370	SK 2,000 Pro-Air	4,200 lbs.				
Optional Features:						
P50330	50 Gallon water tank, mounting kit and pump					
P50246M	Manual spray bar (includes seat and mounting components)					
P50331	Hydraulically driven SandPumper™ II material pump system					
P50246D	Hydraulically operated spray bar (SandPumper II only)					
P50336	Electric Hose Reel: returns spray hose automatically					
P50337	Hand Operated Hose Reel					
P50403	Maxx-Air 2" Diaphragm Pump with 20 HP Compressor					
P50405	2" Air Diaphragm Pump					
P50281B	Night Work Lights					
E9000 * Call for pricing	Blocking / Bracing Charge (if required)	400 lbs.				



SPRAYMASTER SK 1500 WITH CUSTOM TRUCK MOUNTING

AVAILABLE ON PAGE 53

STANDARD FEATURES:



GX390 Honda Engine



Dual Diaphragm Material Pump



One Gallon Basket Strainer



75-foot Hose and Spray Wand

SPECIFICATIONS:

Material Pump:	
TypeDual Diaphr	agm
Inlet / Outlet1	
Air Compressor:	
EngineGX390 Ho	onda
SCFM	30.0

	575	750	1000	1500	2000
Height	60"	68"	76"	76"	76"
Width	48"	56"	64"	64"	64"
Length	144"	144"	144"	174"	204"