

# CLEAR CRACK SEALANT

**CMT-59**

**REVISED 12/19**

## PRODUCT DESCRIPTION & BENEFITS

SportMaster Clear Drying Crack Sealant is a 100% acrylic, clear-drying crack sealant for asphalt, concrete, and existing acrylic sport surfaces. The strong & elastomeric formula seals cracks and dries clear to minimize unsightly repairs while extending the life of asphalt & concrete sport surfaces.

## USES

Tennis, basketball, pickleball, and all other asphalt, concrete, or existing recreational sport & play surfaces.

## COLOR

White, dries clear.

## SURFACE PREPARATION

Cracks must be cleaned of dust, dirt, and debris including vegetation. Blow clean with an air compressor or high pressure washer, as needed.

## APPLICATION

Use product as is. Do not dilute. Best applied with putty knife or trowel. Dry time is dependant upon temperature, humidity and applied thickness. Apply on dry surface when surface and air temperatures are not forecast to drop below 50 degrees F (10°C) during application and for at least 24 hours after application.

## COVERAGE

Approximately 75-150 linear feet per gallon, depending on the width and depth of the crack. Recommended for smaller cracks. If applied in cracks exceeding ¼" in width, product may dry with a slight haze and not completely clear.

## CLEAN UP

Wash tools in water.

## CAUTIONS

Do not store in direct sunlight or where temperatures exceed 100°F. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use. Refer to product Safety Data Sheet (SDS) for additional safety information and precautions.

## WARRANTY

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express

or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright © InFrasys, Inc. All rights reserved. Reproduction of any of this material is strictly prohibited.

ThorWorks Industries, Inc.  
P.O. Box 2277  
Sandusky, OH 44870

Phone: 1-800-326-1994  
FAX: 1-419-626-5477  
[www.sportmaster.net](http://www.sportmaster.net)