



MasterSeal Uses:

- Parking Lots
- Driveways
- · Low-Traffic Roads
- Airports
- Shopping Malls
- Highway Shoulders
- · Low-Speed Roads

MIXING PROCEDURES:

(Based on 100 gallons of MasterSeal Concentrate)

MasterSeal Concentrate	100 gallons
Water	15 - 25 gallons
Top Tuff Polymer Additive	1/2 - 2 gallons
Sand [10-70 mach AES]	200-500 lbs

NOTE: Mix thoroughly in agitated tank and apply by squeegee, brush or spray.

MATERIAL REQUIREMENTS: One gallon of MasterSeal Concentrate will cover approximately 100 - 120 square feet (11.1 to 13.3 square yards) per coat when properly mixed and applied.

NOTE: Coverage rate may vary due to pavement age, porosity, and method of application.

MASTERSEAL™


ASPHALT BASED PAVEMENT SEALER

THE SMART CHOICE FOR PAVEMENT MAINTENANCE

Advantages:

- User friendly no irritating fumes
- Deep, rich black color
- More flexible won't check crack

UNSEALED VS. SEALED



MasterSeal replenishes the binder that is lost through weathering and aging and provides a barrier to moisture intrusion as well as ultraviolet rays, chemicals and salt. MasterSeal beautifies pavement, enhancing the image and curb appeal of commercial properties, home driveways, roadways and more.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
S1010P	5 - Gallon Pail	52 lbs.	\$43.99
S1010D	55 - Gallon Drum	580 lbs.	\$451.99
S1010B	Bulk	-	- quoted -