



## GATORPAVE™

READY-TO-USE PATCHING MATERIAL FOR CRACKED & ALLIGATORING PAVEMENT

**Features:**

- High solids, polymer-modified, fiber reinforced asphalt emulsion designed to fill and repair large cracks and alligatored areas in asphalt pavement
- Fortified with aggregate and recycled rubber particles



PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1160P	5 - Gallon Pail	62 lbs.	\$82.99
M1160D	55 - Gallon Drum	680 lbs.	\$893.99



## TROWEL GRADE CRACK FILLER

HEAVY-BODIED MATERIAL FOR FILLING AND REPAIRING LARGE CRACKS IN PAVEMENT

**Features:**

- Viscous, heavy-bodied trowel grade formulation
- Polymer-modified asphalt emulsion fortified with mineral filler, aggregate and recycled rubber particles for maximum filling and flexible properties



PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1020P	5 - Gallon Pail	65 lbs.	\$60.99



## ACRYLIC CRACK FILLER

THE ULTIMATE CRACK FILLER

**Features:**

- Formulated with 100% tough, durable, elastomeric acrylic polymers
- Outstanding UV and fuel resistance
- Remains flexible at low temperatures
- Designed for use in all cracks including alligatored areas



PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1002G	1 - Gallon Jug	11 lbs.	\$40.99

**MIXING PROCEDURES FOR COLD-APPLIED CRACK SEALANTS, FILLERS, AND PATCHING MATERIALS:**  
Do not dilute. Stir thoroughly.

**MATERIAL REQUIREMENTS (coverage):** Coverage is dependent upon depth and width of cracks. Typically, one gallon of crack filling material will fill approximately 75-150 linear feet of cracks depending on depth and width of cracks