



## ASPHALT BINDER™

AN ASPHALT EMULSION TACK COAT DESIGNED FOR PRIMING BITUMINOUS PAVEMENT SURFACES

### Features:

- Tack coat for patching, paving and coating processes
- Promotes adhesion of bituminous concrete products and coatings
- Meets the ISSA Requirements for SS1H
- Environmentally friendly, water-based formulation

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1140P	5 - Gallon Pail	46 lbs.	\$55.99
M1140D	55 - Gallon Drum	515 lbs.	\$559.99
M1140B	Bulk	-	- quoted -

### MIXING PROCEDURES:

#### Primer for coatings:

Asphalt Binder ..... 10 gallons  
Water ..... 80 gallons

#### For use as a tack coat for patching or paving:

Asphalt Binder ..... 10 gallons  
Water ..... 10 gallons

**MATERIAL REQUIREMENTS (coverage):** Dependent upon water dilution.



## ASPHALT BINDER PLUS™

MULTI-PURPOSE POLYMER-MODIFIED ASPHALT EMULSION FORMULATED FOR ADDED FLEXIBILITY, ADHESION & RESILIENCE

### Uses:

- Asphalt Recycling Agent
- Pavement Rejuvenator/Fog Seal
- Crack Sealant for Road Application
- Tack Coat

*Can also be used as an Economical Crack Sealant for Roads*

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1145P	5 - Gallon Pail	46 lbs.	\$68.99
M1145D	55 - Gallon Drum	515 lbs.	\$709.99
M1145B	Bulk	-	- quoted -

### MIXING PROCEDURES:

**Recycling agent for infrared patching:** Use as is. No dilution required.

**For use as a tack coat for patching or paving:** Dilute 1 to 1 with water. Apply by spray or brush. Apply at a rate of .06 to .10 gallons of mixed material per square yard (.03 to .05 concentrate).

**MATERIAL REQUIREMENTS (coverage):** Reference the Material Specification Sheet.



## TACK AWAY™

LIQUID DETACKIFIER FOR HOT-APPLIED CRACK SEALANTS

### SPRAYABLE BARRIER

### Advantages:

- Eliminates stickiness of freshly applied sealant
- Provides a barrier between tires and fresh sealant
- Compatible with all hot pour crack sealants (Will not attack or harm sealant)
- Reduces traffic down time
- Economical and time saving
- Will not alter or affect sealant properties
- Environmentally-friendly and biodegradable pavement surfaces

**APPLICATION INSTRUCTIONS:** Gently stir Tack Away prior to use. Fill Garden-type, hand-held pump up sprayer with Tack Away. Adjust spray tip to a medium fan pattern. Spray Tack Away directly on freshly applied crack sealant while minimizing overspray onto pavement.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M2000P	5 - Gallon Pail	45 lbs.	\$69.99