



ASK ABOUT COAL TAR ULTRA

FACTORY BLENDED
WITH WATER,
POLYMER ADDITIVE
AND SAND

Coal Tar Pavement Sealer Uses:

- Parking Lots
- Airports
- Driveways
- Shopping Malls

MIXING PROCEDURES:

[Based on 100 gallons of Coal Tar Concentrate]

Coal Tar Concentrate	100 gallons
Water	30-40 gallons
PaveGel Polymer Additive	1-2 gallons
Sand [40-70 mesh AFS]	200-500 lbs.

Mix thoroughly in agitated tank and apply by squeegee, brush or spray.

MATERIAL REQUIREMENTS (coverage): One gallon of Coal Tar Concentrate will cover approximately 100 - 120 square feet [11.1 to 13.3 square yards] per coat when properly mixed and applied.

COAL TAR PAVEMENT SEALER

FORMULATED FOR ADDED FUEL & UV RESISTANCE

Advantages:

- Deep, rich black color
- Oil and fuel resistant
- Reduced fume formulation for user-friendly application

BEAUTIFIES & PROTECTS

SealMaster Coal Tar Sealer is a clay-stabilized, fuel resistant, coal tar emulsion pavement sealer fortified with special surfactants for superior adhesion and durability. SealMaster Coal Tar Sealer is ideal for protecting all types of asphalt pavement surfaces including parking lots, driveways, shopping malls, airports and more. Meets ASTM and Federal specifications.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
S1000P	5 - Gallon Pail	54 lbs.	\$ 37.99
S1000D	55 - Gallon Drum	595 lbs.	\$ 353.99
S1000B	Bulk	-	- quoted -



ASK ABOUT PMCTS ULTRA

FACTORY BLENDED
WITH SAND ADDED

Polymer Modified Coal Tar Sealer Uses:

- Parking Lots
- Airports
- Driveways
- Shopping Malls

MIXING PROCEDURES:

[Based on 100 gallons of PMCTS]

PMCTS	100 gallons
Sand [40-70 mesh AFS]	200-400 lbs.

NOTE: If required, a small amount of water may be added to facilitate application of mixed material.

MATERIAL REQUIREMENTS (coverage): One gallon of PMCTS will cover approximately 85 - 95 square feet [9.4 to 10.5 square yards] per coat when properly mixed and applied.

APPLICATION: For optimum performance and durability, apply two coats of PMCTS with sand. A third coat of PMCTS with sand may be applied to high traffic areas such as entrances, exits and drive lanes.

POLYMER-MODIFIED COAL TAR SEALER (PMCTS)

PREMIUM QUALITY COAL TAR EMULSION PAVEMENT SEALER

POLYMER MODIFIED FOR MAXIMUM DURABILITY

Advantages:

- Highly durable - applied at 48-55% solids (unlike conventional sealers that are applied at 40% solids)
- Dries fast
- Rubberized for added flexibility and adhesion
- Fuel resistant

POLYMER MODIFICATION MAKES THE DIFFERENCE

Polymer-Modified Coal Tar Sealer (PMCTS) is a clay stabilized, fuel resistant coal tar emulsion pavement sealer blended with polymers and special surfactants for superior adhesion, flexibility and durability. PMCTS is ideal for protecting all types of asphalt including parking lots, driveways, shopping malls, airports and more.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
S1096P	5 - Gallon Pail	51 lbs.	\$ 39.99
S1096D	55 - Gallon Drum	565 lbs.	\$ 373.99
S1096B	Bulk	-	- quoted -