



Shown with
optional
storage deck

TR 1000 SPRAYMASTER™ WITH PRO-AIR SYSTEM

A 1,000-GALLON TRAILER MOUNTED
SEALCOAT SPRAY SYSTEM APPLICATOR

**DESIGNED TO MIX AND APPLY PAVEMENT
SEALERS WITH OR WITHOUT SAND.**

TR 1000 Features:

- Dependable, low-maintenance, air-driven dual diaphragm pump. Shifts to neutral automatically when wand or spray bar is shut off. Sprays pavement sealers with sand loadings - 50 GPM.
- 1,000-gallon tank with hydraulically controlled full sweep agitator with rubber wiper blades
- 75-foot hose and spray wand - Spray bar is optional
- Two 8,000 lb. axles, load range G tires
- Running lights and brake lights
- Safety break-away braking system
- One gallon basket strainer



STANDARD FEATURES:



13 HP Honda Engine



Dual Diaphragm
Material Pump



One Gallon Basket
Strainer



Safety Break-Away
Braking System

PRODUCT #	DESCRIPTION	WEIGHT
E1140	TR 1000 Pro-Air	4,560 lbs.
Optional Features:		
P50330	50 Gallon water tank, mounting kit and pump	
P50332	Storage Deck	
P50246M	Manual spray bar (includes seat and mounting components)	
P50247L	Lever - Manual spray bar	
P50331	Hydraulically driven SandPumper II material pump system	
P50246D	Hydraulically operated spray bar (SandPumper II only)	
P50280B	Water Cooler	
P50281B	Night Work Lights	
P50336	Electric Hose Reel: returns spray hose automatically	
P50337	Hand Operated Hose Reel	
T1145	Brush Water Box 40"	
P50405	2" Air Diaphragm Pump	
E9000	Blocking / Bracing Charge (if required)	400 lbs.

* Call for pricing

SPECIFICATIONS:

Height 7' 10"
 Width 80"
 Length with Spray Bar 18'
 Length With Optional Storage Deck 20'
 Spray Bar Width 88"
 Axles 2 - 8,000 lbs.
 Tongue Weight Empty 640 lbs.
 Engine 13 HP Honda
 Material Pump:
 Type Dual Diaphragm
 Inlet / Outlet 1 1/2"
 Air Compressor:
 Engine 13 HP Honda
 SCFM 30.0