



TR 575 & 750 SPRAYMASTER™ WITH PRO-AIR SYSTEM

TRAILER MOUNTED SEALCOAT SPRAY SYSTEM APPLICATORS

DESIGNED TO MIX AND APPLY PAVEMENT SEALER WITH OR WITHOUT SAND

TR 575 & 750 Features:

- Dependable, low-maintenance air-driven dual diaphragm pump. Shifts to neutral automatically when wand or spray bar is shut off. Sprays pavement sealers with sand loadings - 50 GPM.
- 575 or 750-gallon tank with hydraulically controlled, full-sweep agitator with rubber wiper blades
- 75-foot hose and spray wand - Spray bar is optional
- Two 6,000 lb. axles
- Running lights and brake lights
- Safety break-away braking system
- One-gallon basket strainer



PRODUCT #	DESCRIPTION	WEIGHT
E1120	TR 575 Pro-Air	3,810 lbs.
E1132	TR 750 Pro-Air	3,900 lbs.
Optional Features:		
P50332	Storage Deck	
P50246M	Manual spray bar (includes seat and mounting components)	
P50247L	Lever - Manual spray bar	
P50330	50 Gallon water tank, mounting kit and pump	
P50331	Hydraulically driven SandPumper II material pump system	
P50246D	Hydraulically operated spray bar (SandPumper II only)	
P50280B	Water Cooler	
P50281B	Night Work Lights	
P50336	Electric Hose Reel: returns spray hose automatically	
P50337	Hand Operated Hose Reel	
T1145	Brush Water Box 40"	
P50405	2" Air Diaphragm Pump	
E9000	Blocking / Bracing Charge (if required)	400 lbs.

TR 575 SPECIFICATIONS:

Height	73"
Width	75"
Length with Spray Bar	18'
Length with Optional Storage Deck	20'
Spray Bar Width	88"
Axles	2 - 6,000 lbs.
Tongue Weight Empty	380 lbs.
Engine	13 HP Honda
Material Pump:	
Type	Dual Diaphragm
Inlet / Outlet	1 1/2"
Air Compressor:	
Engine	13 HP Honda
SCFM	30.0

TR 750 SPECIFICATIONS:

Height	81"
Width	75"
Length with Spray Bar	18'
Length with Optional Storage Deck	20'
Spray Bar Width	88"
Axles	2 - 6,000 lbs.
Tongue Weight Empty	390 lbs.
Engine	13 HP Honda
Material Pump:	
Type	Dual Diaphragm
Inlet / Outlet	1 1/2"
Air Compressor:	
Engine	13 HP Honda
SCFM	30.0

* Call for pricing