

White Elastomeric Roof Patch

Acrylic Emulsion Patch Material



Revised: 07/10

- Dries White
- Excellent Adhesion & Flexibility
- Acrylic Formula for Lasting Performance

Manufacturer

ThorWorks Industries
 2520 S. Campbell St.
 Sandusky, Ohio
 Phone: 800-326-1994
 Fax: 419-626-5477
 www.sealmaster.net

Description

An acrylic emulsion patch material designed for repairing cracks, seams, edges around skylights, vents, and metal joints. Dries white.

Uses

- Cracks
- Seams
- Skylights
- Vents
- Metal Joints



Surface Preparation

Clean Roof - Sweep off all dirt, dust, and debris. Remove rust, mildew, oil, grease, or other foreign material on the surface. Scrub roof with solution of TSP (Trisodium Phosphate) and water. Remove mold and mildew with bleach solution (1 part chlorine bleach and 3 parts water). Rinse thoroughly and allow to dry.

Application

.9 Gallon Pail: Stir before and during use. With a 4-inch wide paint brush, apply a liberal amount of Elastomeric Roof Patch. Apply Roof Patch 6-inches wide along cracks, seams, or vent areas. Roll White Resin Treated Glass Fabric into wet roof patch. Smooth out fabric with paint brush. While material is still wet, brush another coat of Roof Patch over the Glass Fabric. Make certain the fabric is completely embedded into Roof Patch material. Allow Roof Patch material to dry thoroughly before applying Elastomeric White Reflective Roof Coating.

10 Oz. Tube: Trim nozzle to desired bead size. Puncture foil at innerbase of nozzle. Using a caulking gun, apply to a minimum wet thickness of 1/4". Allow at least 24 hours to dry (70°F and less than 50% humidity with no rain) before applying a surface coating. Use above or below grade.

Drying Time

Dependent on depth of repairs. Typically dries within 24 hours.

Clean Up

Wash tools with water before material dries.

White Elastomeric Roof Patch
 Acrylic Emulsion Patch Material

Form No.: F2070G

Weather Conditions

- Application temperature must be a minimum of 60°F and rising. Do not apply when temperature is expected to drop below 50°F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Dependent upon depth and width of areas to be repaired.

Precautions

- Do Not Heat or Thin
- Do Not Freeze
- Do Not Store at Temperatures Below 50°F

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Packaging

Item #	Container Size	Pack	Weight	Price
F2070G	.9 Gallon Pail	6	71 lbs.	\$ 28.99

*At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary
Limestone	16389-88-1
Titanium Dioxide	13463-67-7
Ester Alcohol	25265-77-4