

# GAME TIME FIELD MARKING PAINT

SMT-334

REVISED 08/11/16

## PRODUCT DESCRIPTION

Game Time Field Marking Paint is a fast-drying latex paint designed for marking playing lines on natural grass athletic fields.

## RECOMMENDED USES

Ideal for all types of natural grass athletic surfaces including football fields, soccer fields, baseball fields, lacrosse fields, rugby fields and more.

## COVERAGE

One 4.75 gallon pail will cover up to 4,500 linear feet for a 4-inch wide stripe at a wet film thickness of 6.4 mils.

## SURFACE PREPARATION

Cut grass to desired height before applying. Ideally, grass should be cut to between 1 and 1.5 inch height for the initial application of paint. This will allow paint to penetrate through the grass to the ground. Grass and ground should be dry prior to application.

## COLOR

White, Yellow, and Neutral (requires tint).

## APPLICATION EQUIPMENT

Spraying is the preferred method of application. Use airless spray equipment set between 1700 and 2,000 psi. Tip size should be a .317 or .319.

## MIXING PROCEDURES

This material is ready to apply. Do not dilute. Stir well before using.

## APPLICATION

Do not apply below 50°F or if rain is imminent. For best results, spray lines in one direction and allow paint to dry. Then spray over same line in the opposite direction. This will provide optimum coverage.

## PROTECT CONTAINERS FROM FREEZING

PRODUCT DATA	
Vehicle Type	Acrylic Co-Polymer Latex emulsion
Weight Solids	32% ± .2 lbs.
Weight / Gallon	10.1 lbs. ± .2 lbs.
VOC	Less than 50 grams per liter
Dry Time	30-60 minutes @ 77°F with 50% relative humidity
Clean Up	Wash tools with water before material dries.

## WARRANTY AND DISCLAIMER

SealMaster warrants that Game Time Field Marking Paint meets the chemical composition and performance requirements set forth in section 4. Liability to the buyer or user of this product is limited to the replacement value of the product only.

The statements made on this specification sheet are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

Form No.: SMT-334

Revised: 08/16

Copyright © 2016, SealMaster

All rights reserved.