



**1. PRODUCT NAME:**

Sport Wax

**2. MANUFACTURER:**

ThorWorks Industries, Inc.  
 2520 S. Campbell St.  
 Sandusky, OH 44870  
 Phone: 800-326-1994  
 Fax: 419-626-5477  
 www.thorworks.com

**Additional Plant Locations:**

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit [www.sealmaster.net](http://www.sealmaster.net) to find the location near you.

**3. PRODUCT DESCRIPTION & BENEFITS:**

Sport Wax is a ready to use, 100% acrylic, clear drying emulsion formulated as a protective top coat for SportMaster Color systems.

**Color:** Clear when dry.

**Uses:** Tennis courts, Basketball courts, and other multi-purpose sport systems.

**4. SURFACE PREPARATION:**

Surface must be cleaned entirely of dust, dirt, and debris.

**5. MIXING PREPARATION:**

Sport Wax is ready to use. DO NOT DILUTE.

**6. APPLICATION:**

Recommended application is by spray (airless power spray or garden type pump). A roller, brush, or squeegee may also be used. Sport Wax should be applied at the rate of 200-300 sq. ft. per gallon.

**7. IMPORTANT:**

Temperatures must be above 50°F both during application and for a period of at least 24 hours after application.

**8. DRYING TIME:**

Sport Wax will be dry to the touch in one hour at 72°F.

**9. COVERAGE:**

A coverage rate of 200-300 sq. ft.

per gallon is recommended. Coverage rates may be affected by surface porosity.

**10. CLEAN UP:** Wash sprayers, tools, etc. in water before material dries.

**11. CAUTIONS:**

KEEP OUT OF REACH OF CHILDREN. Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. When not in use, keep containers tightly closed and upright to prevent leakage.

**9. WARRANTY:**

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is

limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2005, SealMaster  
 All rights reserved.

ThorWorks Industries, Inc.  
 P.O. Box 2277  
 Sandusky, OH 44870

Phone: 1-800-326-1994  
 FAX: 1-419-626-5477

[www.sportmaster.net](http://www.sportmaster.net)

---

### Chemical Characteristics

---

Classification.....	Thermoplastic Acrylic Emulsion
Weight Per Gallon.....	8.5 ± .5 lbs. per gallon
Flammability.....	Non Flammable
Flash Point.....	None
Storage Life.....	Keep liquid from freezing
Color.....	Clear when dry

---