



ASPHALT BINDER™

AN ASPHALT EMULSION TACK COAT DESIGNED FOR PRIMING BITUMINOUS PAVEMENT SURFACES

Features:

- Tack coat for patching, paving and coating processes
- Promotes adhesion of bituminous concrete products and coatings
- Meets the ISSA Requirements for SS1H
- Environmentally friendly, water-based formulation

MIXING PROCEDURES:

Primer for coatings:

Asphalt Binder 10 gallons
 Water 80 gallons

For use as a tack coat for patching or paving:

Asphalt Binder 10 gallons
 Water 10 gallons

MATERIAL REQUIREMENTS (coverage): Dependent upon water dilution.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1140P	5 - Gallon Pail	46 lbs.	\$ 47.99
M1140D	55 - Gallon Drum	515 lbs.	\$ 450.99
M1140B	Bulk	-	- quoted -



ASPHALT BINDER PLUS™

MULTI-PURPOSE POLYMER-MODIFIED ASPHALT EMULSION FORMULATED FOR ADDED FLEXIBILITY, ADHESION & RESILIENCE

Uses:

- Asphalt Recycling Agent
- Pavement Rejuvenator/Fog Seal
- Crack Sealant for Road Application
- Tack Coat

Can also be used as an Economical Crack Sealant for Roads

MIXING PROCEDURES:

Recycling agent for infrared patching: Use as is. No dilution required.

For use as a tack coat for patching or paving: Dilute 1 to 1 with water. Apply by spray or brush. Apply at a rate of .06 to .10 gallons of mixed material per square yard (.03 to .05 concentrate).

MATERIAL REQUIREMENTS (coverage): Reference the Material Specification Sheet.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1145P	5 - Gallon Pail	46 lbs.	\$ 58.99
M1145D	55 - Gallon Drum	515 lbs.	\$ 579.99



HEATED ASPHALT DISTRIBUTORS

AVAILABLE ON PAGE 62 + 63