

#### **MIXING PROCEDURES:**

### Primer for coatings:

Asphalt Binder	10 gallons
Water	.80 gallons

### For use as a tack coat for patching or paving:

Asphalt Binder	10 gallons
Water	10 gallons

**MATERIAL REQUIREMENTS (coverage):** Dependent upon water dilution.

# **ASPHALT BINDER™**

AN ASPHALT EMULSION TACK COAT DESIGNED FOR PRIMING BITUMINOUS PAVEMENT SURFACES

#### Features:

- Tack coat for patching, paving and coating processes
- Promotes adhesion of bituminous concrete products and coatings
- Meets the ISSA Requirements for SS1H
- Environmentally friendly water-based formulation

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1140P	5 - Gallon Pail	46 lbs.	\$ 45.99
M1140D	55 - Gallon Drum	515 lbs.	\$ 420.99
M1140B	Bulk	-	- quoted -



## MIXING PROCEDURES:

**Recycling agent for infrared patching:** Use as is. No dilution required.

For use as a tack coat for patching or paving: Dilute 1 to 1 with water. Apply by spray or brush. Apply at a rate of .06 to .10 gallons of mixed material per square yard [.03 to .05 concentrate].

**MATERIAL REQUIREMENTS** *(coverage)*: Reference the Material Specification Sheet.

# **ASPHALT BINDER PLUS™**

MULTI-PURPOSE POLYMER-MODIFIED ASPHALT EMULSION FORMULATED FOR ADDED FLEXIBILITY, ADHESION & RESILIENCE

## **Uses:**

- · Asphalt Recycling Agent
- Pavement Rejuvenator/Fog Seal
- Crack Sealant for Road Application
- Tack Coat

# Can also be used as an Economical Crack Sealant for Roads

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1145P	5 - Gallon Pail	46 lbs.	\$ 56.99
M1145D	55 - Gallon Drum	515 lbs.	\$ 551.99





HEATED ASPHALT DISTRIBUTORS

AVAILABLE ON PAGE 62