

## CONCRETE SEALER

100% ACRYLIC WATER-BASED EMULSION

**Features:**

- Meets ASTM C309 Type I Class A
- Beautifies concrete
- Protects against moisture penetration and water damage
- Protects against surface scaling and spalling
- Dust-proofs concrete surfaces
- Provides stain and chemical resistance
- Excellent resistance to water blushing (whitening), when exposed to rain or moisture.
- Environmentally friendly, VOC compliant
- Outstanding wearability
- Non-yellowing formula

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1300P	5 - Gallon Pail	46 lbs.	\$104.99
M1300D	55 - Gallon Drum	510 lbs.	\$1,089.99

**MIXING PROCEDURES:** Concrete Sealer is ready-to-use. Do not dilute. Stir thoroughly before applying.

**MATERIAL REQUIREMENTS (coverage):** One gallon of Concrete Sealer will cover 200 square feet.

## CONCRETE PATCH

100% ACRYLIC TROWEL GRADE FORMULA

**Features:**

- Heavy-bodied trowel grade patch material fortified with mineral filler
- Designed for filling larger cracks up to 1" wide in concrete surfaces
- Fills and repairs damaged and spalled areas in concrete up to 1/4" deep
- Ideal for repairing interior and exterior concrete surfaces
- Environmentally friendly, water-based formula

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1350G	1 - Gallon Pail	17 lbs.	\$29.99

**MIXING PROCEDURES:** Use as is. Do not dilute. Stir thoroughly before applying.

**MATERIAL REQUIREMENTS (coverage):** One gallon of Concrete Patch will fill approximately 75-150 feet of cracks depending on depth and width of crack. When used to patch low spots, coverage will vary with depth of patch.

## CONCRETE PATCH BINDER

LIQUID ACRYLIC BINDING AGENT FOR SAND AND CEMENT MIXES

**Features:**

- 100% acrylic emulsion designed for mixing with cement powder and sand
- Produces a patch mix with superior flexural, adhesive, and impact strength
- Excellent adhesion to concrete and masonry
- Resistance to many industrial chemicals
- Environmentally friendly, water-based formulation
- Provides lasting repair for concrete surfaces
- Ideal for thin overlays and repairs up to 1/2" thick

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1340P	5 - Gallon Pail	47 lbs.	\$187.99
M1340D	55 - Gallon Drum	525 lbs.	\$2,027.99

**MIXING PROCEDURES:**

Concrete Patch Binder.....	3.5 gallons
Sand.....	100 lbs.
Portland Cement.....	15 - 20 lbs.
Water.....	up to 1/2 gallon if needed

(Additional water may be required to achieve workability)

**MATERIAL REQUIREMENTS:** One gallon of Concrete Patch Binder will produce enough patch mix [when mixed with sand and cement] to fill .86 square yard [approximately 7.75 sq. ft.] at 1/4" depth.

## CONCRETE CRACK SEALANT

100% ACRYLIC EMULSION CRACK SEALANT

**Features:**

- Designed for filling cracks in concrete surfaces
- Environmentally friendly 100% acrylic, water-based emulsion
- Outstanding flexibility - remains flexible at temperatures below 0°F
- High solids formula for less shrinkage
- Packaged in one gallon jugs

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1355G	1 - Gallon Jug	15 lbs.	\$41.99

**MIXING PROCEDURES:** Use as is. Do not dilute.

**MATERIAL REQUIREMENTS (coverage):** Typically, one gallon of Concrete Crack Sealant will fill approximately 75-150 feet of cracks.