

CONCRETE SEALER

100% ACRYLIC WATER-BASED EMULSION

Features:

- Meets ASTM C309 Type I Class A
- Beautifies concrete
- Protects against moisture penetration and water damage
- Protects against surface scaling and spalling
- Dust-proofs concrete surfaces
- Provides stain and chemical resistance
- Excellent resistance to water blushing (whitening), when exposed to rain or moisture.
- Environmentally friendly, VOC compliant
- Outstanding wearability
- Non-yellowing formula

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1300P	5 - Gallon Pail	46 lbs.	\$ 75.99
M1300D	55 - Gallon Drum	510 lbs.	\$ 750.99

MIXING PROCEDURES: Concrete Sealer is ready-to-use. Do not dilute. Stir thoroughly before applying.

MATERIAL REQUIREMENTS (coverage): One gallon of Concrete Sealer will cover 200 square feet.

CONCRETE PATCH

100% ACRYLIC TROWEL GRADE FORMULA

Features:

- Heavy-bodied trowel grade patch material fortified with mineral filler
- Designed for filling larger cracks up to 1" wide in concrete surfaces
- Fills and repairs damaged and spalled areas in concrete up to 1/4" deep
- Ideal for repairing interior and exterior concrete surfaces
- Environmentally friendly, water-based formula

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1350G	1 - Gallon Pail	17 lbs.	\$ 22.99

MIXING PROCEDURES: Use as is. Do not dilute. Stir thoroughly before applying.

MATERIAL REQUIREMENTS (coverage): One gallon of Concrete Patch will fill approximately 75-150 feet of cracks depending on depth and width of crack. When used to patch low spots, coverage will vary with depth of patch.

CONCRETE PATCH BINDER

LIQUID ACRYLIC BINDING AGENT FOR SAND AND CEMENT MIXES

Features:

- 100% acrylic emulsion designed for mixing with cement powder and sand
- Produces a patch mix with superior flexural, adhesive, and impact strength
- Excellent adhesion to concrete and masonry
- Resistance to many industrial chemicals
- Environmentally friendly, water-based formulation
- Provides lasting repair for concrete surfaces
- Ideal for thin overlays and repairs up to 1/2" thick

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1340P	5 - Gallon Pail	47 lbs.	\$ 119.99
M1340D	55 - Gallon Drum	525 lbs.	\$ 1,236.99

MIXING PROCEDURES:

Concrete Patch Binder..... 3.5 gallons
 Sand.....100 lbs.
 Portland Cement.....15 - 20 lbs.
 Water5 gallon

(Additional water may be required to achieve workability)

MATERIAL REQUIREMENTS: One gallon of Concrete Patch Binder will produce enough patch mix [when mixed with sand and cement] to fill .86 square yard [approximately 7.75 sq. ft.] at 1/4" depth.

CONCRETE CRACK SEALANT

100% ACRYLIC EMULSION CRACK SEALANT

Features:

- Designed for filling cracks in concrete surfaces
- Environmentally friendly 100% acrylic, water-based emulsion
- Outstanding flexibility - remains flexible at temperatures below 0°F
- High solids formula for less shrinkage
- Packaged in one gallon jugs

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1355G	1 - Gallon Jug	15 lbs.	\$ 30.99

MIXING PROCEDURES: Use as is. Do not dilute.

MATERIAL REQUIREMENTS (coverage): Typically, one gallon of Concrete Crack Sealant will fill approximately 75-150 feet of cracks.