

CRACKMASTER®

PREMIUM QUALITY HOT POUR CRACK SEALANTS

CRACKMASTER SUPREME DF

Our finest hot-applied crack filling material. Designed for use in both direct-fire and oil-jacketed kettles. Ideal for all crack filling applications on driveways and parking lots.

| PRODUCT # | DESCRIPTION | PRICE |
|-----------|------------------------|-----------------|
| M1050L | CrackMaster Supreme DF | \$ 1.64 per lb. |

CRACKMASTER 3405

Meets ASTM 3405 Specifications. Designed for use in oil-jacketed kettles. Ideal for use on roads and highways. Cold climates - flexible to -20°F. Meets ASTM D 6690 Type II (formerly ASTM D 3405).



| PRODUCT # | DESCRIPTION | PRICE |
|-----------|------------------|-----------------|
| M1060L | CrackMaster 3405 | \$ 1.53 per lb. |

* Also available in state modified formula containing no crumb rubber [CrackMaster 3405 NR] or elevated levels of crumb rubber [CrackMaster 3405 R]*

PREMIUM QUALITY HOT-POUR CRACK SEALANTS

Features:

- Superior performance
- Outstanding flexibility
- Rapid setup time
- Economical to use



CRACKMASTER COVERAGE RATES

| CRACK WIDTH | CRACK DEPTH | LBS. / 100 FT. |
|-------------|-------------|----------------|
| 3/8" | 3/8" | 7 lbs. |
| 1/2" | 1/2" | 13 lbs. |
| 3/4" | 3/4" | 29 lbs. |

CRACKMASTER 3405 LM

Designed for use in oil-jacketed kettles. Ideal for use on roads and highways. Very cold climates - flexible to -40°F.

| PRODUCT # | DESCRIPTION | PRICE |
|-----------|---------------------|-----------------|
| M1060LM | CrackMaster 3405 LM | \$ 1.69 per lb. |

CRACKMASTER TRAFFIC LOOP SEALANT

Premium quality hot-melt loop sealant that resists tracking at elevated temperatures and remains flexible down to temperatures of -10°F. Can also be used in expansion joints and cracks. Recommended for oil-jacketed kettles.

| PRODUCT # | DESCRIPTION | PRICE |
|-----------|----------------------------------|-----------------|
| M1051L | CrackMaster Traffic Loop Sealant | \$ 1.55 per lb. |

CRACKMASTER PL

An economical, high-softening-point material designed for use on parking lots and roads. Recommended for oil-jacketed kettles. Warm climates - flexible to 0°F.

| PRODUCT # | DESCRIPTION | PRICE |
|-----------|----------------|-----------------|
| M1070L | CrackMaster PL | \$ 1.39 per lb. |

CRACKMASTER PL-HT

An economical, high-softening-point material designed for use on parking lots and roads. Recommended for oil-jacketed kettles. Hotter climates - flexible to 20°F.

| PRODUCT # | DESCRIPTION | PRICE |
|-----------|-------------------|-----------------|
| M1071L | CrackMaster PL-HT | \$ 1.46 per lb. |

CRACKMASTER PARKING LOT GRADE

A premium quality crack and joint sealing material that resists tracking at elevated temperatures and remains flexible down to -10°F. Designed for use in direct-fired kettles with agitation and oil-jacketed kettles. Ideal for large parking lots.

| PRODUCT # | DESCRIPTION | PRICE |
|-----------|-------------------------------|-----------------|
| M1075L | CrackMaster Parking Lot Grade | \$ 1.63 per lb. |

CRACKMASTER PARKING LOT GRADE - LP

A premium quality crack and joint sealing material that resists tracking at elevated temperatures and remains flexible down to 0°F. Designed for use in direct-fired kettles with agitation and oil-jacketed kettles. Less surface tack than standard parking lot formulas, lower penetration at elevated temperatures.

| PRODUCT # | DESCRIPTION | PRICE |
|-----------|------------------------------------|-----------------|
| M1074L | CrackMaster Parking Lot Grade - LP | \$ 1.58 per lb. |