

OIL SPOT PRIMERS

Seals oil, gas, and grease spots on pavement prior to sealcoating. Helps prevent oil spots from bleeding up through freshly applied pavement sealer.



PREP SEAL™

READY-TO-USE OIL SPOT PRIMER

Features:

- Ready-to-use acrylic-based emulsion forms barrier over oil and grease spots
- Helps prevent oil and grease spots from bleeding up through freshly applied pavement sealer
- Applied by roller, brush, or spray
- Environmentally friendly, water-based formulation

| PRODUCT # | DESCRIPTION | WEIGHT | PRICE |
|-----------|-----------------|---------|----------|
| M1130G | 1 - Gallon Jug | 9 lbs. | \$ 21.99 |
| M1130P | 5 - Gallon Pail | 46 lbs. | \$ 47.99 |

MIXING PROCEDURES: Prep Seal is a ready-to-use product. Do not dilute. Use as is. Stir thoroughly before applying.

MATERIAL REQUIREMENTS (coverage): One gallon of Prep Seal will cover approximately 150-200 square feet.



PETRO SEAL™

CONCENTRATED OIL SPOT PRIMER

Features:

- Concentrated, acrylic-based emulsion forms barrier over oil and grease spots
- Helps prevent oil and grease spots from bleeding up through freshly applied pavement sealer
- Applied by roller, brush, or spray
- Can be diluted up to 2 parts water to 1 part Petro Seal
- Environmentally friendly, water-based formulation

| PRODUCT # | DESCRIPTION | WEIGHT | PRICE |
|-----------|------------------|----------|-------------|
| M1120P | 5 - Gallon Pail | 47 lbs. | \$ 114.99 |
| M1120D | 55 - Gallon Drum | 520 lbs. | \$ 1,243.99 |

MIXING PROCEDURES: Can be diluted up to one part Petro Seal and two parts water. However, a 1 to 1 dilution rate is typically recommended. Mix thoroughly before applying.

MATERIAL REQUIREMENTS (coverage): One gallon of Petro Seal when mixed 1 to 1 with water will cover approximately 300-400 square feet.