

# OIL SPOT PRIMERS

Seals oil, gas, and grease spots on pavement prior to sealcoating. Helps prevent oil spots from bleeding up through freshly applied pavement sealer.



## PREP SEAL™

### READY-TO-USE OIL SPOT PRIMER

#### Features:

- Ready-to-use acrylic-based emulsion forms barrier over oil and grease spots
- Helps prevent oil and grease spots from bleeding up through freshly applied pavement sealer
- Applied by roller, brush, or spray
- Environmentally friendly, water-based formulation

**MIXING PROCEDURES:** Prep Seal is a ready-to-use product. Do not dilute. Use as is. Stir thoroughly before applying.

**MATERIAL REQUIREMENTS (coverage):** One gallon of Prep Seal will cover approximately 150-200 square feet.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1130G	1 - Gallon Jug	9 lbs.	\$ 17.99
M1130P	5 - Gallon Pail	46 lbs.	\$ 40.99



## PETRO SEAL™

### CONCENTRATED OIL SPOT PRIMER

#### Features:

- Concentrated, acrylic-based emulsion forms barrier over oil and grease spots
- Helps prevent oil and grease spots from bleeding up through freshly applied pavement sealer
- Applied by roller, brush, or spray
- Can be diluted up to 2 parts water to 1 part Petro Seal
- Environmentally friendly, water-based formulation

**MIXING PROCEDURES:** Can be diluted up to one part Petro Seal and two parts water. However, a 1 to 1 dilution rate is typically recommended. Mix thoroughly before applying.

**MATERIAL REQUIREMENTS (coverage):** One gallon of Petro Seal when mixed 1 to 1 with water will cover approximately 300-400 square feet.

PRODUCT #	DESCRIPTION	WEIGHT	PRICE
M1120P	5 - Gallon Pail	47 lbs.	\$ 94.99
M1120D	55 - Gallon Drum	520 lbs.	\$ 964.99