



Shown with storage deck

TR 1000 SPRAYMASTER™ WITH PRO-AIR SYSTEM

A 1,000-GALLON TRAILER MOUNTED SEALCOAT SPRAY SYSTEM APPLICATOR

DESIGNED TO MIX AND APPLY PAVEMENT SEALERS WITH OR WITHOUT SAND.

TR 1000 Features:

- Dependable, low-maintenance, air-driven dual diaphragm pump. Shifts to neutral automatically when wand or spray bar is shut off. Sprays sand-filled pavement sealers.
- 1,000-gallon tank with hydraulically controlled full sweep agitator with rubber wiper blades
- 75-foot hose and spray wand - Spray bar is optional
- Two 8,000 lb. axles, load range G tires
- Running lights and brake lights
- Safety break-away braking system
- One gallon basket strainer



STANDARD FEATURES:

GX390 HP
Honda EngineDual Diaphragm
Material PumpOne Gallon Basket
StrainerSafety Break-Away
Braking System

| PRODUCT # | DESCRIPTION | WEIGHT |
|---------------------------|--|------------|
| E1140 | TR 1000 Pro-Air | 4,200 lbs. |
| E1140XD | TR 1000 Pro-Air Extended Deck | 4,560 lbs. |
| Optional Features: | | |
| P50330 | 50 Gallon water tank, mounting kit and pump | |
| P50246M | Manual spray bar (includes seat and mounting components) | |
| P50247L | Lever - Manual spray bar | |
| P50331 | Hydraulically driven SandPumper II material pump system | |
| P50246D | Hydraulically operated spray bar (SandPumper II only) | |
| P50280B | Water Cooler | |
| P50281B | Night Work Lights | |
| P50336 | Electric Hose Reel: returns spray hose automatically | |
| P50337 | Hand Operated Hose Reel | |
| T1145 | Brush Water Box 40" | |
| P50405 | 2" Air Diaphragm Pump | |
| E9000 | Blocking / Bracing Charge (if required) | 400 lbs. |

* Call for pricing

SPECIFICATIONS:

Height7' 10"
 Width80"
 Length with Spray Bar18'
 Length With Optional Storage Deck20'
 Spray Bar Width88"
 Axles2 - 8,000 lbs.
 Tongue Weight Empty640 lbs.
 EngineGX390 Honda
 Material Pump:
 TypeDual Diaphragm
 Inlet / Outlet1 1/2"
 Air Compressor:
 EngineGX390 Honda
 SCFM30.0