

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : CrackMaster Mastic - CPT (Mastic T2 - CPT, Mastic Parking Lot - CPT), CrackMaster Bridge Joint Mastic - CPT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : sealant/surface repair

1.3. Details of the supplier of the safety data sheet

ThorWorks Industries, Inc
 2520 S. Campbell St.
 Sandusky, OH 44870
 1-800-326-1994

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Carc. 1B H350 Full text of H-phrases: see section 16

2.2. Label elements GHS-US labelling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger
 Hazard statements (GHS-US) : H350 - May cause cancer
 Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P280 - Wear eye protection, face protection, protective clothing, protective gloves
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P405 - Store locked up
 P501 - Dispose of contents/container to an authorized waste collection point

2.3. Other hazards

Other hazards not contributing to the classification : Risk of thermal burns on contact with molten product.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not Applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Extracts (petroleum), heavy paraffinic distillate solvent	(CAS No) 64742-04-7	0.1 – 20	Carc. 1B, H350
Carbon black	(CAS No) 1333-86-4	0 – 5	Carc. 2, H351*

*Bound, not available to inhale as dust

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
 First-aid measures after inhalation : Remove victim to fresh air & keep at rest in position comfortable for breathing. Get medical advice/attention.
 First-aid measures after skin contact : Drench affected area with water for at least 15 minutes.
 First-aid measures after eye contact : Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart.
 First-aid measures after ingestion : Get medical advice/attention if you feel unwell.

CrackMaster Mastic - CPT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause cancer.
Symptoms/injuries after inhalation : Inhalation of vapors may cause respiratory irritation.
Symptoms/injuries after skin contact : Heated product causes burns.
Symptoms/injuries after eye contact : Heated product causes burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Class B. Carbon dioxide. Dry chemical. Foam. Water spray.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : When heated, material emits irritating fumes. Burning produces irritating, toxic and noxious fumes.
Explosion hazard : Product is not explosive.
Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

Firefighting instructions : Do not allow run-off from fire fighting to enter drains/water courses. Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all eye and skin contact and do not breathe vapor and mist. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.
Emergency procedures : Stop leak if safe to do so.

6.2. Environmental precautions

Do not discharge into drains or the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop the flow of material, if this is without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Allow molten material to cool. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing vapors. Avoid contact with skin and eyes. Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use.
Incompatible products : Strong oxidizers.
Incompatible materials : Heat sources.
Prohibitions on mixed storage : Keep away from incompatible materials.
Storage area : Store in dry, cool, well-ventilated area.

CrackMaster Mastic - CPT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.3. Specific end use(s) sealant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CrackMaster Binder		
ACGIH	Not applicable	
OSHA	Not applicable	
Extracts (petroleum), heavy paraffinic distillate solvent (64742-04-7)		
ACGIH	Not applicable	
OSHA	Not applicable	
Carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m³)	3.5 mg/m³
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m³)	3.5 mg/m³

8.2. Exposure controls

Appropriate engineering controls : Avoid creating mist or spray. Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air).
Use only outdoors or in a well-ventilated area.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Insulated gloves.

Eye protection : Chemical goggles or safety glasses. Contact with hot material - risk of serious burns. Face shield.

Skin and body protection : Long sleeved protective clothing. Foot protection.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Appropriate self-contained breathing apparatus may be required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Liquid. Temperatures above. Softening point.

Color : Black dark brown

Odor : petroleum

Odor threshold : No data available

pH : No data available

Melting point : 65.5 - 121.1 °C (150 - 250 °F)

Freezing point : No data available

Boiling point : > 315.6 °C (> 600 °F)

Flash point : > 204.4 °C (> 400 °F)

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : No data available

Explosive limits : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Vapor pressure : No data available

Relative density : 1 - 1.9

Relative vapor density at 20 °C : No data available

Density : 8 - 16 lbs/gal

Solubility : No data available

Log Pow : No data available

Log Kow : No data available

Auto-ignition temperature : > 371.1 °C (> 700 °F)

Decomposition temperature : No data available

Viscosity : No data available

CrackMaster Mastic - CPT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity No dangerous reactions known.

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid None known.

10.5. Incompatible materials Strong oxidizing agents.

10.6. Hazardous decomposition products Aldehydes. aromatic hydrocarbons. Carbon monoxide. hydrogen sulphide. Burning produces irritating, toxic and noxious fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation

Acute toxicity : Not classified

Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m ³ 4 h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust
National Toxicology Program (NTP) Status	Not listed in carcinogenicity class

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : Not classified
Symptoms/injuries after inhalation : Inhalation of vapors may cause respiratory irritation.
Symptoms/injuries after skin contact : Heated product causes burns.
Symptoms/injuries after eye contact : Heated product causes burns.

SECTION 12: Ecological information

12.1. Toxicity No additional information available

12.2. Persistence and degradability

Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential No additional information available

12.4. Mobility in soil No additional information available

12.5. Other adverse effects No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

CrackMaster Mastic - CPT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT) In accordance with DOT; Not considered a dangerous good for transport regulations

Additional information

Other information : No supplementary information available.

ADR No additional information available

Transport by sea No additional information available

Air transport No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Extracts (petroleum), heavy paraffinic distillate solvent (64742-04-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Extracts (petroleum), heavy paraffinic distillate solvent (64742-04-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Extracts (petroleum), heavy paraffinic distillate solvent (64742-04-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Carbon black (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Carc. 1B H350

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

National regulations

Carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on Taiwan National Chemical Inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).

15.3. US State regulations

Carbon black (1333-86-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Carbon black (1333-86-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Indication of changes : Original Document.

CrackMaster Mastic - CPT

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Data sources : ACGIH (American Conference of Government Industrial Hygienists).
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Kristen Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
OSHA 29CFR 1910.1200 Hazard Communication Standard.
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.
- Abbreviations and acronyms : ATE: Acute Toxicity Estimate.
CAS (Chemical Abstracts Service) number.
CFR: Code of Federal Regulations.
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population.
OSHA: Occupational Safety & Health Administration.
TSCA: Toxic Substances Control Act.
- Other information : None.

Full text of H-phrases:

Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
H350	May cause cancer
H351	Suspected of causing cancer

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 1 - Must be preheated before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



SDS US (GHS HazCom 2012)

SDS prepared by: The Redstone Group, LLC.
6077 Frantz Rd
Suite 206
Dublin, Ohio, USA 43016
614.923.7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product