

# Non-Fibered Roof and Foundation Coating

## Asphalt Based Coating

- Penetrates, Preserves, & Protects Roofs, Foundations, Wood Fences, Barns, & More
- Use for Coating Entire Surface Area, Above or Below Grade
- Meets ASTM D 41



Revised: 07/10

### Manufacturer

ThorWorks Industries  
2520 S. Campbell St.  
Sandusky, Ohio  
Phone: 800-326-1994  
Fax: 419-626-5477  
www.sealmaster.net

### Description

A sealer-preserved for all types of surfaces, this product is an excellent saturant for composition roofing which has become excessively dry. It rustproofs metal, preserves wood, waterproofs stone or brick and rejuvenates composition surfaces. Also used to coat concrete foundations, above or below grade as well as fences and barns. Dries black.

### Uses

- Most Roof Surfaces, Concrete Foundations, Wood Fences and Barns



### Surface Preparation

For best results, clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts. Repair any leaking or weak areas with SealMaster All Weather Roof Cement and SealMaster Asphalt Coated Reinforcing Fabric repair material.

### Application

Stir before and during use. Coat entire surface area with SealMaster Non-Fibered Roof and Foundation Coating. Material may be brushed or sprayed using a minimum 500 psi airless sprayer. Porous surfaces may require two applications. Do not apply on any wet surface.

### Drying Time

Allow 24 hours depending on weather conditions.

### Clean Up

Clean tools with mineral spirits or kerosene in a well ventilated area immediately after use.

### Coverage (Approximate)

- Metal Surfaces: 90-100 sq. ft. per gallon
- Concrete and Masonry Surfaces: 75-100 sq. ft. per gallon
- Wood or Composition: 65-90 sq. ft. per gallon
- Worn Roofing: 50-80 sq. ft. per gallon

### Precautions

- Do Not Heat or Thin
- Do Not Store at Temperatures Above 100°F
- Do Not Apply Over Coal Tar Surfaces
- Do Not Apply Where Hydrostatic Pressures Could Be Encountered
- Combustible. Contains Petroleum Distillate

### Safety And Environmental

Non-Fibered Roof and Foundation Coating  
Asphalt Based Coating

Form No.: F2035P

## Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 300 gm/liter max
- Use With Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN

## Packaging

Item #	Container Size	Pack	Weight	Price
F2035P	4.75 Gallon Pail	1	42 lbs.	\$ 43.99

\*At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7