



Acrylic Adhesion Promoter

CMT - 21

Revised: 2/10

1. PRODUCT NAME:

Acrylic Adhesion Promoter

2. MANUFACTURER:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477
www.thorworks.com

Additional Plant Locations:

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit www.sealmaster.net to find the location near you.

3. PRODUCT DESCRIPTION & BENEFITS:

Acrylic Adhesion Promoter is a clear drying, one part water based acrylic emulsion. It is designed to prime asphalt and concrete pavement surfaces and promote the adhesion of SportMaster Acrylic Color Coating Products.

Color: Blue. Clear when dry.

4. SURFACE PREPARATION:

• **Asphalt:** Pavement surface must be cleaned entirely of dust, dirt, debris and all loose materials. Repair of pavement surface defects, depressions and cracks should be complete prior to application.

• **Concrete:** New concrete surfaces must cure 28 days prior to application. Concrete surfaces should have a medium broom finish or similar roughened texture. Etch surface with phosphoric or muriatic acid and rinse thoroughly with water. Allow concrete to dry completely before applying Acrylic Adhesion Promoter.

5. MIXING PROCEDURES:

Stir thoroughly before using. Apply Acrylic Adhesion Promoter as is. DO NOT DILUTE.

6. APPLICATION:

Use roller, spray, or broom to apply. Apply a thin coat of Acrylic Adhesion Promoter at the rate of

200 - 300 square feet per gallon. Do not leave excess build-up of material on surface. Allow Acrylic Adhesion Promoter to dry completely before applying SportMaster Coating Products.

7. IMPORTANT:

Stir before using. Temperatures must be above 50°F both during application and for a period of at least 24 hours after application. Do not apply when rain is imminent or forecast. Keep from freezing. Close container when not in use.

8. DRYING TIME:

Forty-Five to Ninety (45 -90) minutes under optimum conditions.

9. COVERAGE:

Approximately 200 - 300 square feet per gallon depending on surface porosity.

10. CAUTIONS:

KEEP OUT OF REACH OF CHILDREN. Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. When not in use, keep containers tightly closed and upright to prevent leakage.

11. WARRANTY:

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied,

concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2010, SealMaster
All rights reserved.

ThorWorks Industries, Inc.
P.O. Box 2277
Sandusky, OH 44870

Phone: 1-800-326-1994
FAX: 1-419-626-5477

www.sportmaster.net

Chemical Characteristics

Classification.....	Acrylic Emulsion
Weight per gallon at 77°F.....	8.7 ± .5 pounds
Flammability.....	Non Flammable
Flash Point.....	None
Storage Life.....	One Year