



Asphalt Binder

CMT - 12

Revised: 4/05

1. PRODUCT NAME:

Asphalt Binder

2. MANUFACTURER:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477
www.thorworks.com

Additional Plant Locations:

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit www.sealmaster.net to find the location near you.

3. PRODUCT DESCRIPTION & BENEFITS:

SportMaster Asphalt Binder is an anionic asphalt emulsion.

Color: Available in Black.

4. USES:

Apply to old oxidized asphalt track surfaces prior to the application of TrackMaster to achieve better coating adhesion.

5. SURFACE PREPARATION:

Pavement surface must be cleaned entirely of dust, dirt, debris and all loose material.

6. MIXING PROCEDURES:

Dilute 1 part Asphalt Binder with 5 parts water. Mix to a uniform consistency.

7. APPLICATION:

Asphalt Binder can be brushed or sprayed onto surface.

8. IMPORTANT:

Stir before using. Temperatures must be above 50° F both during application and for a period of at least 24 hours after application. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use. On outdoor concrete surfaces, assure adequate and functional perimeter drains as well as a sound vapor barrier beneath the slab.

9. DRYING TIME:

30 to 60 minutes under optimum drying conditions.

10. COVERAGE:

.02 to .04 gallons per square yard. Yield calculations are based on undiluted gallons of Asphalt Binder.

12. CAUTIONS:

KEEP OUT OF REACH OF CHILDREN. Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. When not in use, keep containers tightly closed and upright to prevent leakage.

13. WARRANTY:

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control.

Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2005, SealMaster
All rights reserved.

ThorWorks Industries, Inc.
P.O. Box 2277
Sandusky, OH 44870

Phone: 1-800-326-1994
FAX: 1-419-626-5477

www.sportmaster.net

Chemical Characteristics

Asphalt Emulsion (63.8% Non Volatile).....100% Weight (minimum)

Product Data

Type	Asphalt Emulsion
Pounds per Gallon @ 77° F.....	8.55 ± .5 lbs.
% Non Volatile Material	63.90 ± 3 lbs.
Odor	Asphalt
Flammability.....	Non-Flammable
Flash Point.....	None
Storage Life.....	One Year
Colors	Black

Asphalt Binder
CMT - 12

SealMaster
April 2005
(Supersedes CMT-12 (6/97), CMT-12 (12/02), CMT-12 (7/04))

SPORT SURFACING