



**1. PRODUCT NAME:**

Stripe-Rite

**2. MANUFACTURER:**

ThorWorks Industries, Inc.  
 2520 S. Campbell St.  
 Sandusky, OH 44870  
 Phone: 800-395-7325  
 Fax: 419-626-5477  
 www.thorworks.com

**Additional Plant Locations:**

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit [www.sealmaster.net](http://www.sealmaster.net) to find the location near you.

**3. PRODUCT DESCRIPTION & BENEFITS:**

Stripe-Rite is a 100% acrylic clear drying emulsion primer for line striping. Stripe-Rite is applied prior to SportMaster Line Paint to fill the minor voids between the masking tape and the court surface to assure crisp, razor sharp lines.

**Color:** Milky White. Clear when dried.

**Uses:** For priming line markings on any bituminous, concrete or color coated surface.

**4. SURFACE PREPARATION:**

Pavement Surface must be cleaned of dust, dirt, debris and all loose material.

**5. APPLICATION:**

Stripe-Rite can be rolled, brushed or sprayed with low pressure spraying equipment. Allow Stripe-Rite to dry completely before applying SportMaster Line Paint.

**6. IMPORTANT:**

Stir before using. Temperatures must be above 50°F. both during application and for a period of at least 24 hours after application. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use.

**7. DRYING TIME:**

Thirty to sixty (30 to 60) minutes under optimum drying conditions.

Indoor applications are substantially affected by temperature and available ventilation and will dry more slowly.

**8. COVERAGE:**

450 to 500 lineal feet of 2 inch line per gallon.

**9. CLEAN-UP:**

Wash sprayers, tools, etc. in water before material dries.

**10. CAUTION:**

Do not store in direct sunlight or where temperatures exceed 100°F. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use.

**11. WARRANTY:**

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized

and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2005, SealMaster  
 All rights reserved.

ThorWorks Industries, Inc.  
 P.O. Box 2277  
 Sandusky, OH 44870

Phone: 1-800-326-1994  
 FAX: 1-419-626-5477

[www.sportmaster.net](http://www.sportmaster.net)

**Chemical Characteristics:**

	% Weight (Nominal)
Acrylic Emulsion .....	38.0
Hiding Pigment.....	0.0
Mineral Inert Fillers.....	7.0
Film Former, Additives .....	1.5
Water.....	50.0

**Product Data:**

Type .....	Acrylic Emulsion
Weight per gallon at 77°F.....	8.9 ± .5
% Non Volatile Material.....	29 ± 5
Odor .....	Slight Ammonia
Flammability.....	Non-Flammable
Flash Point.....	None
Storage Life .....	One Year
Colors.....	Milky White, clear when dry